

LED OMNIDIRECTIONAL A-LAMP A19 NON-DIM SERIES GEN 3



9W & 11W



15W



PRODUCT DESCRIPTION:

MaxLite's LED Omnidirectional A-Line lamp replicate true A19 incandescents that produces even light in all directions. They are suited to a wide variety of residential and commercial applications, pendants, wall sconces and table and floor lamps.

FEATURES:

- 9 Watts (60W Equivalent, 800 Lumens)
- 11 Watts (75W Equivalent, 1100 Lumens)
- 15 Watts (100W Equivalent, 1600 Lumens)
- 25,000 hour life (L70 standards)
- CCT: 2700K & 3000K Standard (4000K & 5000K, special order only. Please call MaxLite for more information.)
- CRI: ≥ 80
- Non-Dimmable
- Saves more than 84 percent on energy
- Power factor: ≥0.6
- Standard E26 base
- ENERGY STAR certified
- Mercury-free
- RoHS Compliant
- 5 year standard warranty

APPLICATIONS

- Table and floor lamps
- Sconces
- Approved for use in totally enclosed fixtures or recessed lighting
- Suitable for use in damp locations

WARRANTY:

5-year standard warranty
(further details available at www.maxlite.com/warranties)

ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: E9A19ND30/G3	
FAMILY	BASE	DIMMABILITY	CCT
E9A19= Enclosed 9 watts, A19 E11A19= Enclosed 11 watts, A19 E15A19= Enclosed 15 watts, A19	(OMIT)= E26	ND= Non-Dimmable	27/G3= 2700K Gen 3 30/G3= 3000K Gen #

NOTES:

1. 3000K models are available in 9W & 15W only

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference.
- (2) This device must accept any interference received, including interference that may cause undesired operation.

SPECIFICATIONS:

ITEM	SPECIFICATION	DETAILS		
		9A19NDxx/G3	11A19NDxx/G3	15A19NDxx/G3
GENERAL PERFORMANCE	Power Consumption	9W	11W	15W
	Lumens Delivered	800	1,100	1,600
	Efficacy (lm/w)	89	100	106
	CRI	≥ 82		
	Color Temperature (CCT)	2700K, 3000K	2700K	2700K, 3000K
	Lumen Maintenance (L70)	25,000 Hours		
	Dimmable	No		
ELECTRICAL	Power Factor	≥0.6		
	Input Voltage	120V		
PHYSICAL	Base Type	E26		
	Operating Temperature	-4°F - 104°F		
CERTIFICATION	Environment	Dry, Damp		
	Warranty	5 year standard warranty		

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL NUMBER	ENERGY STAR	INPUT WATTAGE	EQUIVALENT WATTAGE	DELIVERED LUMENS	EFFICACY (lm/W)	CRI	CCT (K)	DIMENSIONS (D" x MOL")
E26 Base									
14099661	E9A19ND27/G3	★	9	60W Inc.	800	89	82	2700K	2.36" x 4.25"
14099663	E9A19ND30/G3	★	9	60W Inc.	800	89	83	3000K	
14099662	E9A19ND27/G3/4P	★	9	60W Inc.	800	89	82	2700k	
14099664	E11A19ND27/G3	★	11	75W Inc.	1100	100	84	2700K	
14099666	E15A19ND27/G3	★	15	100W Inc.	1600	106	84	2700K	2.36" x 4.55"
14099668	E15A19ND30/G3	★	15	100W Inc.	1600	106	84	3000K	

★ ENERGY STAR certified