



Easy J-Box Installation Constant Voltage LED Driver Phase-Cut Dimmable

# **Specification Sheet**


The E-Series EZ96 is an electronic Class 2 dimmable LED driver designed to easily conceal in standard 4" junction boxes.

- Lighting applications: Under-cabinet, kick/cove, furniture, merchandise cases, and more
- Easy code compliant J-Box installations with low-voltage/main voltage divider
- Dimmable down to 1%
- Uses popular forward phase TRIAC dimmers
- Auto reset, over current and short circuit protection

Installation: Wire leads Driver Types: Class 2, Single Channel Dimming: Phase-cut dimmable down to 1% with leading edge TRIAC dimmer Input Voltage: 120VAC, 50/60Hz Output Voltage: 24VDC Listing: UL Recognized Certifications: UL 8750, CSA C22.2 No. 250 13-14 Warranty: 5 year

ORDERING GUIDE					
Туре	Max Power	Listing	Output		
EZ96	<b>96</b> – 96W	R – UL Recognized	<b>24DC</b> – 24VDC		

DRIVER & INSTALL KIT ORDERING GUIDE				
Part Number	Kit Description			
EZ96R24DC-JBKIT	Driver + J-Box Kit			
EZ96R24DC-LVD	Driver + Low-Voltage Divider Kit			
EZ96R24DC-BKT	Driver + Bracket Kit			
EZ96R24DC	Driver Only			





# **E-SERIES EZ96**

Easy J-Box Installation **Constant Voltage LED Driver Phase-Cut Dimmable** 


## **Specification Sheet**

	PART NO.	KIT DESCRIPTION
1	EZ96R24DC-JBKIT	Driver + J-Box Kit
2	EZ96R24DC-LVD	Driver + Low-Voltage Divider Kit
3	EZ96R24DC-BKT	Driver + Bracket Kit

1

### Kit includes:

- EZ96 Driver
- Low-voltage divider
- 4" J-Box
- Wire connectors (4)
- Cable clamps (2)
- J-Box cover (not shown)



EZ96R24DC-LVD 2 Driver + Low-Voltage Divider Kit

#### Kit includes:

- EZ96 Driver
- · Low-Voltage divider

#### Supplied by others:


- 4" J-Box and cover
- wire connectors
- cable clamps

#### EZ96R24DC-BKT 3

Driver + Bracket Kit

#### Kit includes:

- EZ96 Driver
- Mounting bracket
- #8 one-inch screws (2)
- Washers (2)




SPECIFICATIONS					
INPUT	96W				
Input Voltage Range	120VAC ± 10%				
Input Frequency	50 / 60Hz				
Input Current	0.85A@120VAC				
Efficiency	> 90%				
Power Factor	0.95				
OUTPUT					
Maximum Load	96W				
Minimum Load	8W				
Output Voltage @ Max. Load	24.0 VDC				
Output Current @ Max. Load	4.16A				
ENVIRONMENTAL					
Max. Ambient Temperature	-30°C to +40°C (-22°F to 104°F)				
Ingress Protection	IP54, Dust/water spray				
DIMMING	n of, Dust/water spray				
Minimum Dimming Level	1%				
PROTECTION	1 /0				
Circuit Breaker	Short-circuit & over- voltage auto-reset				
MECHANICAL HOUSING					
Primary Leads	18AWG				
Secondary Leads	14AWG				
Length	3.63" (92mm)				
Width	2.54" (64.5mm)				
Height	0.89" (22.6mm)				
Weight	9 oz. (255g)				
Housing Material	Coated Steel				
APPROVAL MARKINGS					
<b>Certifications/Approval Signs</b>	UL8750 Class 2				





Easy J-Box Installation Constant Voltage LED Driver Phase-Cut Dimmable **Specification Sheet** 


**MECHANICAL DIAGRAMS** 






**E-SERIES EZ96** 

Easy J-Box Installation Constant Voltage LED Driver Phase-Cut Dimmable **Specification Sheet** 



### $\Psi$ LOAD REGULATION $\Psi$



**MAGNITUDE** LIGHTING